

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (original) A production process for producing a plurality of semiconductor devices on chip areas which are defined on a wafer, which production process comprises:

processing said wafer such that each of said chip areas is produced as a semi-finished semiconductor device by forming a first wiring-arrangement section on each of said chip areas;

subjecting said wafer to a provisional yield-rate test in which it is examined whether each of the semi-finished semiconductor devices on said wafer is acceptable or unacceptable; and

further processing said wafer such that each of said chip areas is produced as a finished semiconductor device by forming a second wiring-arrangement section on said first wiring-arrangement section when said wafer passes said provisional yield-rate test.

2. (original) A production process as set forth in claim 1, wherein a yield-rate of acceptable semi-finished semiconductor devices is found in said provisional yield-rate test, and it is determined that said wafer has passed said

provision yield-rate test when said yield-rate exceeds a predetermined permissible rate.

3. (original) A production process as set forth in claim 1, wherein said first wiring-arrangement section is formed as a basic wiring-arrangement section to define plural kinds of basic electronic component formation areas in each of said chip areas, and said second wiring-arrangement section is formed as a customized wiring-arrangement section to establish electrical interconnections among said basic electrical component formation areas in accordance with a customer's request.

4. (currently amended) A production process as set forth in claim ~~[[1]]~~ 3, wherein said basic wiring-arrangement section has a plurality of electrode pads formed on an uppermost surface thereof, for carrying out said provisional yield-rate test.

5. (original) A production process as set forth in claim 1, further comprising:

subjecting said wafer to a genuine yield-rate test in which it is examined whether each of the finished semiconductor devices on said wafer is acceptable or unacceptable to thereby find a yield-rate of acceptable finished semiconductor devices; and

finally processing said wafer when said wafer passes said genuine yield-rate test.

6. (original) A production process as set forth in claim 5, wherein a yield-rate of acceptable finished semiconductor devices is found in said genuine yield-rate test, and it is determined that said wafer has passed said genuine yield-rate test when said yield-rate exceeds a predetermined permissible rate.

7. (currently amended) A production process as set forth in claim 5, wherein said ~~customized~~ second wiring-arrangement section has a plurality of electrode pads formed on an uppermost surface thereof, and said genuine yield-rate test is carried out, using the electrode pads of said ~~customized~~ second wiring-arrangement section.

8. (currently amended) A production process as set forth in claim 7, wherein said ~~[[basic]]~~ first wiring-arrangement section is formed as a multi-layered wiring-arrangement section composed of at least two metal circuit pattern layers and at least one insulation layer alternately laminated on each of said chip areas, and said ~~customized~~ second wiring-arrangement section is formed as a multi-layered wiring-arrangement section composed of at least two metal circuit pattern layers and at least one insulation layer alternately laminated on said ~~[[basic]]~~ first wiring-arrangement section.

9-23. (canceled)

24. (new) A process for producing a plurality of semiconductor devices on chip areas of a wafer, said process comprising:

forming a first wiring-arrangement section on each of the chip areas, said first wiring-arrangement section having a first test section;

performing a provisional yield-rate test using a respective first test section to determine whether each of said first wiring-arrangement section is acceptable or unacceptable; and

forming a second wiring-arrangement section on said first wiring-arrangement section when said wafer passes said provisional yield-rate test, said second wiring-arrangement section having a second test section that is different from and connected to said first wiring-arrangement section.

25. (new) The process as set forth in claim 24, wherein said first wiring-arrangement section has a plurality of electrode pads formed on an uppermost surface thereof, for carrying out said provisional yield-rate test.

26. (new) The process as set forth in claim 24, further comprising:

performing a genuine yield-rate test using said second test section to determine whether each of said second wiring-arrangement section is acceptable or unacceptable to thereby find a yield-rate of acceptable finished semiconductor devices; and processing said wafer when said wafer passes said genuine yield-rate test.

27. (new) The process as set forth in claim 26, wherein said second wiring-arrangement section has a plurality of electrode pads formed on an uppermost surface thereof, said genuine yield-rate test being carried out using the electrode pads of said second wiring-arrangement section.

28. (new) The process as set forth in claim 24, wherein said step of forming said first wiring-arrangement section comprises forming a multi-layered wiring-arrangement section comprising at least two metal circuit pattern layers and at least one insulation layer alternately laminated on each of said chip areas, and

wherein said step of forming said second wiring-arrangement section comprises forming a multi-layered wiring-arrangement section comprising at least two metal circuit pattern layers and at least one insulation layer alternately laminated on said first wiring-arrangement section.

29. (new) A production process for producing a plurality of semiconductor devices on chip areas which are defined on a wafer, said production process comprises:

processing said wafer such that each of said chip areas is produced as a semi-finished semiconductor device by forming a first wiring-arrangement section on each of said chip areas, each said first wiring-arrangement section having a first test section electrically connected to an active region of a respective one of said chip areas;

subjecting said wafer to a provisional yield-rate test using said first test section to determine whether each of said semi-finished semiconductor devices on said wafer is acceptable or unacceptable; and

further processing said wafer such that each of said chip areas is produced as a finished semiconductor device by forming a second wiring-arrangement section on said first wiring-arrangement section when said wafer passes said provisional yield-rate test, each said second wiring-arrangement section having a second test section, different than said first test section, that is electrically connected to said active region of a corresponding one of said chip areas.